

Лист тех. данных

3VL9431-6NA40

ETU VL400, 4-pole, line protection ETU10, LI IR=126...315A, overload protection, II=1.25 to 11xIN, short-circuit protection, N protected screw terminal connections in scope of delivery of switching unit



версия

торговая марка изделия
 наименование изделия

SENTRON
 расцепитель макс. тока

Механическая конструкция

масса нетто

2,23 kg

General Product Approval

EMC

Declaration of Conformity

[Miscellaneous](#)

[Confirmation](#)



Test Certificates

Marine / Shipping

other

[Special Test Certificate](#)



[Confirmation](#)

[Miscellaneous](#)

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6NA40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6NA40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6NA40

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>



