

Лист тех. данных

3VL9431-6SG30



ETU VL400, 3-pole, line protection ETU22, LSIG 3 phases/3 lines
IR=126...315A, overload protection, ISD=1.5 to 10xIR, II=11 xIN short-circuit protection screw terminal connections in scope of delivery of switching unit

версия		
торговая марка изделия	SENTRON	
наименование изделия	расцепитель макс. тока	
Механическая конструкция		
масса нетто	1,67 kg	
General Product Approval	EMC	Declaration of Conformity

[Miscellaneous](#)

[Confirmation](#)



Test Certificates	Marine / Shipping	other
Special Test Certificate 		Miscellaneous Confirmation

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6SG30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6SG30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6SG30

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



