

Лист тех. данных

3VL9431-6SH30



ETU VL400, 3-pole, line protection ETU22, LSIG 3 phases/4 lines with connecting cable IR=126...315A, overload protection, ISD=1.5 to 10xIR, II=11 xIN short-circuit protection screw terminal connections in scope of delivery of switching unit

версия	
торговая марка изделия	SENTRON
наименование изделия	расцепитель макс. тока
Механическая конструкция	
масса нетто	1,68 kg
General Product Approval	EMC Declaration of Conformity

[Miscellaneous](#)

[Confirmation](#)



Test Certificates	Marine / Shipping	other
Special Test Certificate		Miscellaneous Confirmation

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6SH30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6SH30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6SH30

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>



