

Лист тех. данных

3VL9431-6SS30

ETU VL400, 3-pole, motor protection ETU30M, LI IR=126...315A, overload protection, TC=10A...30, time lag class II=6/8/11 xIN, short-circuit protection screw terminal connections in scope of delivery of switching unit



версия

торговая марка изделия
наименование изделия

SENTRON
расцепитель макс. тока

Механическая конструкция

масса нетто 1,76 kg

General Product Approval

EMC

Declaration of Conformity

[Miscellaneous](#)

[Confirmation](#)



Test Certificates

Marine / Shipping

other

[Special Test Certificate](#)



[Miscellaneous](#)

[Confirmation](#)

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6SS30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6SS30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6SS30

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>



