

Лист тех. данных

3VL9431-6TE40



ETU VL400, 4-pole, line protection ETU20, LSI IR=126...315A, overload protection, ISD=1.5 to 10xIR, II=11 xIN short-circuit protection, N unprotected screw terminal connections in scope of delivery of switching unit

версия		
торговая марка изделия		SENTRON
наименование изделия		расцепитель макс. тока
Механическая конструкция		
масса нетто		2,07 kg
General Product Approval		EMC
		Declaration of Conformity

[Miscellaneous](#)

[Confirmation](#)



Test Certificates	Marine / Shipping	other
Special Test Certificate   		Miscellaneous Confirmation

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6TE40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6TE40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6TE40

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



