

Лист тех. данных

3VL9431-6UL30

ETU VL400, 3-pole, line protection LCD ETU42, LSIG 3 phases/3 lines
IR=126...315A, overload protection, ISD=1.5 to 10xIR, II=11 xIN short-circuit protection screw terminal connections in scope of delivery of switching unit



версия		
торговая марка изделия	SENTRON	
наименование изделия	расцепитель макс. тока	
Механическая конструкция		
масса нетто	1,82 kg	
General Product Approval	EMC	Declaration of Conformity

[Confirmation](#)

[Miscellaneous](#)



Test Certificates	Marine / Shipping	other
Special Test Certificate		Confirmation Miscellaneous

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6UL30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6UL30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6UL30

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>



