

Лист тех. данных

3VL9431-6UP30

ETU VL400, 3-pole, motor/generator prot. LCD ETU40M, LI IR=26...315A, overload protection, ISD=1.5 to 10xIR, II=11 xIN short-circuit protection screw terminal connections in scope of delivery of switching unit



версия		
торговая марка изделия		SENTRON
наименование изделия		расцепитель макс. тока
Механическая конструкция		
масса нетто		1,81 kg
General Product Approval		EMC
		Declaration of Conformity

[Confirmation](#)

[Miscellaneous](#)



EG-Konf.

Test Certificates	Marine / Shipping	other
Special Test Certificate	PRS RINA RMRS	Confirmation Miscellaneous

Environment

[Environmental Confirmations](#)

Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VL9431-6UP30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3VL9431-6UP30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9431-6UP30

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



