

Data sheet

6AG1455-2AD00-4AA0



Figure similar

SIPLUS D455-2 DP/PN based on 6AU1455-2AD00-0AA0 with conformal coating, 0...+55 °C, SIPLUS Drive-based Control Unit D455-2 DP/PN; programmable motion control system; ultra-high performance; interfaces: 12 DI, 16 DI/DQ, 6 DRIVE-CLiQ 3 PROFIBUS, 3 PROFINET ports, 3 Ethernet, 2 USB, 2 option slots; including double fan/battery module and battery

product brand name	SIPLUS
product type designation	D455-2 DP/PN SIPLUS
Performance class for motion control system	ULTRA-HIGH Performance
Version of the motion control system	Multiple-axis system

PLC and motion control performance

number of axes / maximum	128
Minimum PROFIBUS cycle clock	1 ms
Minimum PROFINET send cycle clock	0.25 ms
Minimum interpolator cycle clock	0.25 ms
Minimum servo cycle clock	0.25 ms
• note	0.125 ms (only with ET 200SP, SCOUT TIA V4.5 or higher and SERVO-FAST)

Integrated drive control / header

Maximum number of axes for integrated drive control	
• servo	6
• vector	6
• V/f	12
• note	Alternative control modes; drive control based on SINAMICS S120 CU320-2, firmware version V4.x/V5.x

Memory

RAM (work memory)	388 Mbyte
Additional RAM work memory for Java applications	20 Mbyte
RAM disk (load memory)	90 Mbyte
Retentive memory	512 kbyte
Persistent memory (user data on CF)	1.5 Gbyte

Communication

Interfaces	
• DRIVE-CLiQ	6
• USB	2
• Industrial Ethernet	2
• PROFIBUS	2
— note	Equidistant and isochronous; Can be configured as master or slave
• PROFINET	1
— note	1 interface with 3 ports onboard; 1 interface with 4 ports optional via CBE30-2; functionality: supports PROFINET IO with IRT and RT; configurable as PROFINET IO Controller and/or Device; supports media redundancy (MRP and MRPD)

General technical data

Fan	Wert fehlt
DC supply voltage	
• rated value	24 V

• minimum • maximum	20.4 V
consumed current / typical	28.8 V
• note	1 900 mA
Making current, typ.	with no load on inputs/outputs, no 24 V supply via DRIVE-CLiQ and PROFIBUS interface
Power loss, typ.	5 A
Ambient temperature, during	46 W
• long-term storage • transport • operation — note	-25 ... +55 °C -40 ... +70 °C 0 ... 55 °C Maximum installation altitude 4000 m (13124 ft) above sea level. Above an altitude of 2000 m (6562 ft), the maximum ambient temperature decreases by 7 °C (12.6 °F) per 1000 m (3281 ft).
Relative humidity	0 ... 100 %
• during operation • without condensation, tested acc. to IEC 60068-2-38	condensation/frost permitted (no commissioning in bedewed state)
Product property / Conformal coating	Yes
Resistance	Yes
• to biologically active substances, / conformity acc. to EN 60721-3-3 — Note • to chemically active substances, / conformity acc. to EN 60721-3-3 — Note	Class 3B2 mold and fungal spores (except fauna); For operation, the plug covers included in delivery must be left on the unused interfaces! Yes Class 3C4 incl. salt spray in accordance with EN 60068-2-52 (severity 3); the supplied plug covers must remain in place on the unused interfaces during operation.
Air pressure	620 ... 1 060 hPa
Degree of protection	IP20 / UL open type
height	380 mm
width	50 mm
• depth • Depth / Note	270 mm
net weight	When the spacer is removed 230 mm (9.05 in) deep 4 300 g

Digital inputs / header

number of digital inputs	12
DC input voltage	
• rated value • for signal "1" • for signal "0"	24 V 15 ... 30 V -3 ... +5 V
Electrical isolation	Yes
• note	Yes, in groups of 6
Current consumption for "1" signal level, typ.	9 mA
Input delay time for	
• signal "0" → "1", typ. • signal "1" → "0", typ.	50 µs 150 µs

Digital inputs/outputs / header

Number of digital I/Os	16
Parameterization possibility of the digital I/Os	can be parameterized - as DI - as DO - as probe input (max. 16) - as cam output (max. 8)

If used as an input / header

DC input voltage	
• rated value • for signal "1" • for signal "0"	24 V 15 ... 30 V -3 ... +5 V
Electrical isolation	No
Current consumption for "1" signal level, typ.	9 mA
Input delay time for	
• signal "0" → "1", typ. • signal "1" → "0", typ.	5 µs 50 µs
Measuring input / reproducibility	5 µs
Measuring input / resolution	1 µs

If used as an output / header

Load voltage	24 V
• rated value	20.4 V
• minimum	28.8 V
• maximum	No
Electrical isolation	No
Current carrying capacity for each output, max.	500 mA
Leakage current, max.	2 mA
Output delay for	
• signal "0" → "1", typ.	150 µs
• signal "0" → "1", max.	400 µs
• signal "1" → "0", typ.	75 µs
• signal "1" → "0", max.	150 µs
— note	Data for Vcc = 24 V; load 48 Ohm; "1" = 90 % VOut, "0" = 10 % VOut
Cam output	
• reproducibility	10 µs
• resolution	1 µs
Switching frequency of the outputs for	
• resistive load, max.	4 kHz
• inductive load, max.	2 Hz
• lamp load, max.	11 Hz
Short-circuit protection	Yes
Additional technical data	
Back-up of non-volatile data	
• of retentive data	unlimited buffer duration
• of real-time clock, min.	4 d
• note	longer buffer duration of the real-time clock using a battery inserted in the double fan/battery module
Approvals	
• USA	cULus
• Canada	cULus
• Australia	RCM (formerly C-Tick)
• Korea	No
• Russia, Belarus and Kazakhstan	EAC

